

INDUSTRIAL COMPONENT DATA

BSLK 16 0810012 PHOENIX CONTACT Ground modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: BSLK 16



Manufacturer	PHOENIX CONTACT
MPN / Reference	BSLK 16
Catalog number	0810012
Category	Ground terminal block
Minimum order	10 Pcs
Document ID	EO-3EA7144C64
Generated	2026-08-06

Product Overview

Ground modular terminal block

Ground terminal, number of connections: 2, number of poles: 1, type of connection: Screw connection, cross-section: 0.5 mm² - 16 mm², mounting class: NS 35/7.5, NS 35/15, color: silver

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0810012

Packing unit 10 pc

Minimum order quantity 10 pc

GTIN 4017918007935

Weight per Piece (excluding packing) 13.340 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of positions 1

Number of levels 1

Number of connections 2

Color silver

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Open side panel Yes

Dimensions

Width 8 mm

Length 50 mm

Height NS 35/7,5 34 mm

Height NS 35/15 41.5 mm

Connection data

Note Please observe the current carrying capacity of the DIN rails.

Connection method Screw connection

Connection in acc. with standard IEC 60947-7-2

Conductor cross section solid min. 0.5 mm²

Conductor cross section solid max. 16 mm²

Conductor cross section AWG min. 20

Conductor cross section AWG max. 6

Conductor cross section flexible min. 0.5 mm²

Conductor cross section flexible max. 10 mm²

Min. AWG conductor cross section, flexible 20

Max. AWG conductor cross section, flexible 8

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 10 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 10 mm²

2 conductors with same cross section, solid min. 0.5 mm²

2 conductors with same cross section, solid max. 4...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BSLK 16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.