

INDUSTRIAL COMPONENT DATA

BT 5,5 3281133 PHOENIX CONTACT Feed-through modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: BT 5,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	BT 5,5
Catalog number	3281133
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-4564553D81
Generated	2026-07-29

Product Overview

Feed-through modular terminal block

Feed-through terminal block, nominal voltage: 690 V, nominal current: 41 A, connection type: Annular cable terminal, number of connections: 2, width: 11 mm, color: black, mounting class: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

Key Commercial Data

Orderkey 3281133

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4055626406824

Weight per Piece (excluding packing) 14.680 g

Custom tariff number 85369010

Country of origin IN (India)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 6 mm²
Color black
Insulating material PC
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group IIIa
Maximum power dissipation for nominal condition 1.02 W
Ambient temperature (operation) -40 °C ... 110 °C
Maximum load current 41 A
Nominal current I_N 41 A
Nominal voltage U_N 690 V
Open side panel Yes
Dimensions
Width 11 mm
Length 50.2 mm
Height NS 35/7,5 41 mm
Height NS 35/15 48.5 mm
Connection data
Connection method Ring cable lug
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 6 mm²
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 6 mm²
Min. AWG conductor cross section, flexible 24
Max. AWG conductor cross section, flexible 10
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.2 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 6 mm²
Cable lug connection according to standard DIN 46234
Min. cross section for cable lug connection 0.14 mm²
Max. cross section for cable lug connection 6 mm²
AWG min 26
AWG max 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BT 5,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.