


INDUSTRIAL COMPONENT DATA

BTO 14 3281182 PHOENIX CONTACT Feed-through modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: BTO 14



Manufacturer	PHOENIX CONTACT
MPN / Reference	BTO 14
Catalog number	3281182
Category	Feed-through terminal block
Minimum order	25 Pcs
Document ID	EO-1393AE4DF8
Generated	2026-07-31

Product Overview

Feed-through modular terminal block

Feed-through rail terminal block, with hole for air screws, nominal voltage: 690 V, nominal current: 76 A, connection type: Annular cable terminal, number of connections: 2, width: 15 mm, color: black, mounting class: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 3281182

Packing unit 25 pc

Minimum order quantity 25 pc

Note Made to Order (non-returnable)

GTIN 4055626406916

Weight per Piece (excluding packing) 24.680 g

Custom tariff number 85369010

Country of origin IN (India)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 16 mm²
Color black
Insulating material PC
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group IIIa
Maximum power dissipation for nominal condition 2.43 W
Ambient temperature (operation) -40 °C ... 110 °C
Maximum load current 76 A
Nominal current I_N 76 A
Nominal voltage U_N 690 V
Open side panel Yes
Dimensions
Width 15 mm
Length 59 mm
Height NS 35/7,5 45.2 mm
Height NS 35/15 52.7 mm
Connection data
Connection method Ring cable lug
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 16 mm²
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 16 mm²
Min. AWG conductor cross section, flexible 20
Max. AWG conductor cross section, flexible 6
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 16 mm²
Cable lug connection according to standard DIN 46234
Min. cross section for cable lug connection 0.5 mm²
Max. cross section for cable lug connection 16 mm²
AWG min 20
AWG max...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BTO 14 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.