

INDUSTRIAL COMPONENT DATA

BTO 3,5 3281114 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: BTO 3,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	BTO 3,5
Catalog number	3281114
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-DA1ED1C48A
Generated	2026-08-05

Product Overview

Feed-through terminal block

Feed-in terminal, with hole for air screws, nominal voltage: 690 V, nominal current: 32 A, connection type: Annular cable terminal, number of connections: 2, width: 10 mm, color: black, mounting class: NS 35/7.5, NS 35/15

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data

Orderkey 3281114

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 390 (C-1-2017)

GTIN 4055626118086

Weight per Piece (excluding packing) 11.000 g

Custom tariff number 85369010

Country of origin IN (India)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 4 mm²

Color black

Insulating material PC

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group IIIa

Maximum power dissipation for nominal condition 1.02 W

Ambient temperature (operation) -40 °C ... 110 °C

Maximum load current 32 A

Nominal current I_N 32 A

Nominal voltage U_N 690 V

Open side panel Yes

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Note regarding shock protection Finger safety is only guaranteed with cover profile.

Result of surge voltage test Test passed

Surge voltage test setpoint 7.3 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.89 kV

Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed

Result of bending test Test passed

Bending test rotation speed 10 rpm

Bending test turns 135

Bending test conductor cross section/weight 0.5 mm² / 0.3 kg
4 mm² / 0.9 kg

Tensile test result Test passed

Conductor cross section tensile test 0.5 mm²

Tractive force se...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BTO 3,5 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.