

INDUSTRIAL COMPONENT DATA

BTO 38-4L-F 3281211 PHOENIX CONTACT Feed-through modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: BTO 38-4L-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	BTO 38-4L-F
Catalog number	3281211
Category	Feed-through terminal block
Minimum order	4 Pcs
Document ID	EO-CF0117E3AA
Generated	2026-08-04

Product Overview

Feed-through modular terminal block

Feed-through rail terminal, 4 units, locked with cover with clamping flange, nominal voltage: 690 V, nominal current: 125 A, connection type: Annular cable terminal, number of connections: 8, width: 77.2 mm, height: 51 mm, color: black, mounting type: Direct mounting with a flange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 3281211

Packing unit 4 pc

Note Made to Order (non-returnable)

GTIN 4055626406985

Weight per Piece (excluding packing) 22.220 g

Custom tariff number 85369010

Country of origin IN (India)

General

Number of levels 1

Number of connections 8

Potentials 4

Nominal cross section 35 mm²
Color black
Insulating material PC
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group IIIa
Maximum power dissipation for nominal condition 4.06 W (the value is based on one connection block and is multiplied according to the pin assignment)
Ambient temperature (operation) -40 °C ... 110 °C
Maximum load current 125 A
Nominal current I_N 125 A
Nominal voltage U_N 690 V
Open side panel Yes
Dimensions
Width 77.2 mm
Length 108.4 mm
Height 51 mm
Height NS 35/7,5 66 mm
Height NS 35/15 58.5 mm
Pitch 26 mm
Connection data
Connection method Ring cable lug
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 1.5 mm²
Conductor cross section solid max. 35 mm²
Conductor cross section flexible min. 1.5 mm²
Conductor cross section flexible max. 35 mm²
Min. AWG conductor cross section, flexible 20
Max. AWG conductor cross section, flexible 2
Conductor cross section flexible, with ferrule with plastic sleeve min. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 35 mm²
Cable lug connection according to standard DIN 46235
Min. cross section for cab...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BTO 38-4L-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.