


INDUSTRIAL COMPONENT DATA

BTP 2,0-F 3281112 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: BTP 2,0-F



Manufacturer	PHOENIX CONTACT
MPN / Reference	BTP 2,0-F
Catalog number	3281112
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-B888EC0CE7
Generated	2026-08-02

Product Overview

Feed-through terminal block

Feed-through terminal, with flange on the left side, nominal voltage: 690 V, nominal current: 24 A, connection type: Push-in connection, number of connections: 4, cross-section: 0.14 mm² - 2.5 mm², AWG: 26 - 14, width: 17.5 mm, color: black, mounting class: NS 35/7.5, NS 35/15, Direct mounting with a flange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 3281112

Packing unit 50 pc

Note Made to Order (non-returnable)

GTIN 4055626620596

Weight per Piece (excluding packing) 9.620 g

Custom tariff number 85369010

Country of origin IN (India)

General

Number of levels 1

Number of connections 4

Potentials 1

Nominal cross section 2.5 mm²
Color black
Insulating material PC
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group IIIa
Maximum power dissipation for nominal condition 0.77 W
Ambient temperature (operation) -40 °C ... 110 °C
Maximum load current 24 A (The maximum load current must not be exceeded by the total current of all connected conductors.)
Nominal current I_N 24 A
Nominal voltage U_N 690 V
Open side panel Yes
Dimensions
Width 17.5 mm
Length 42 mm
Height NS 35/7,5 36.7 mm
Height NS 35/15 44.2 mm
Pitch 8 mm
Connection data
Connection method Push-in connection
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 14
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 2.5 mm²
Min. AWG conductor cross section, flexible 26
Max. AWG conductor cross section, flexible 16
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.14 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BTP 2,0-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.