

INDUSTRIAL COMPONENT DATA

BTP 2043W 1050387 PHOENIX CONTACT Touch panel with 10,92 cm / 4,3"-TFT-display (analog resistive (polyester))..

Brand: PHOENIX CONTACT | Manufacturer Part Number: BTP 2043W



Manufacturer	PHOENIX CONTACT
MPN / Reference	BTP 2043W
Catalog number	1050387
Category	Graphic panel
Minimum order	1 Pcs
Document ID	EO-6ADA92D375
Generated	2026-08-02

Product Overview

Touch panel with 10,92 cm / 4,3"-TFT-display (analog resistive (polyester)), 480 x 272 pixel(s) (WQVGA), 262144 colors, Arm9™ i.MX28, 454 MHz, 2x COM (RS-232/422/485), 1x USB 2.0, Typ A, 1x USB 2.0, Typ B, 1 x Ethernet (10/100 Mbps), RJ45, Windows

Touch panel with 10.92 cm / 4.3" TFT-display (analog-resistive), 480 x 272 pixel(s) (WQVGA), 16.7 million colors, Arm® Cortex-A7®, 528MHz i.MX6 UL, 2x COM (RS-232/422/485), 1x USB 2.0, Typ A, 1x USB 2.0, Typ B, 1x Ethernet (10/100 MBits/s), RJ45, Windows® Embedded Compact 7 and user software: Visu+. (Bus system: SIN)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Control Systems (CST)

Additional Product Information

Key Commercial Data

Orderkey 1050387

Packing unit 1 pc

Catalog page Page 471 (C-6-2019)

GTIN 4055626666587

Weight per Piece (excluding packing) 320.000 g

Custom tariff number 84714100

Country of origin IN (India)

Note

Display

General

Device supply

Environmental Product Compliance

Dimensions

Computer data

Ambient conditions

Standards and Regulations

Classifications

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

[Back to top](#)Dimensions

Outer dimensions: width, height, depth 120 mm x 89 mm x 5 mm (Dimensions of the front plate)

Installation dimensions: width, height, depth 111 mm x 80 mm x 31.5 mm (Installation cutout)

[Back to top](#)Display

Display 10,92 cm / 4,3"-TFT

Screen resolution 480 x 272 Pixel(s) (WQVGA)

Touch technology analog resistive (polyester)

Brightness 400 cd/m², typical (adjustable)

Backlighting LED

Display backlight MTBF 20000 h

Colors 262144 colors

Reading angle left 70 °

Reading angle right 70 °

Reading angle top 50 °

Reading angle bottom 70 °

[Back to top](#)Computer data

Processor Arm9™ i.MX28, 454 MHz

Operating system Windows®CE 6.0

User software Visu+

RAM 128 MB DDR2 SDRAM

Mass storage Flash, 512 MB

Network 1 x Ethernet (10/100 Mbps), RJ45

Interfaces 2x COM (RS-232/422/485)

1x USB 2.0, Typ A

1x USB 2.0, Typ B

Bus system without

Slots 1x SD

[Back to top](#)General

Material front plate Plastic

Housing material Plastic

Mounting type Front installation

Weight 200 g

[Back to top](#)Ambient conditions

Degree of protection IP...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BTP 2043W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.