

INDUSTRIAL COMPONENT DATA

SAC-4P-M 8MR/ 5,0-950/M 8FR 1551008 PHOENIX CONTACT

Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M 8MR/ 5,0-950/M 8FR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M 8MR/ 5,0-950/M 8FR
Catalog number	1551008
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-38C8617CE9
Generated	2026-08-02

Product Overview

Bus system cable

Bus system cable, INTERBUS, 4-pole halogen-free, shielded, M8 angled connector, coding: A, to M8 angled female, cable length: 5 m

Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug angled M8, coding: A, on Socket angled M8, coding: A, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Application Standard

Sensor type INTERBUS

Number of positions 4

No. of cable outlets 1

Shielded yes

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

InterfacesBus system INTERBUS

Signal type/category INTERBUS
SignalingStatus display no
Status display present No
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Test voltage 800 V
Transmission medium Copper
Material specificationsFlammability rating according to UL 94 HB
Seal material NBR
Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Connection dataPin assignment
Contact Color (signal designation) Contact (optional) 1 (Plug) RD (0.34 mm²) 1 (Socket)
3 (Plug) BU (0.34 mm²) 3 (Socket)
2 (Plug) YE (0.14 mm²) 2 (Socket)
4 (Plug) GN (0.14 mm²) 4 (Socket)
ConnectorConnection 1
Type Plug angled M8
Number of positions 4
Coding type A (Standard)
Connection 2
Type Socket angled M8
Number of positions 4
Coding type A
Cable/lineCable length 5 m
INTERBUS [950]
Cable weight 41 kg/km
UL AWM Style 20963 (80°C/30 V)
Number of positions 4
Shielded yes
Cable type INTERBUS [950]
Conductor structure 2xAWG26/19+2xAWG22/19
Conductor structure signal line 19x 0.10 mm
AWG signal line 26
Conductor cross section 2x 0.14 mm² (Signal l...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M 8MR/ 5,0-950/M 8FR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.