

INDUSTRIAL COMPONENT DATA

SAC-5P- 5,0-923/FR CAN SCO 1419035 PHOENIX CONTACT

Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-5,0-923/FR CAN SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-5,0-923/FR CAN SCO
Catalog number	1419035
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-E49315F50F
Generated	2026-08-04

Product Overview

Bus system cable

Bus system cable, CANopen®, DeviceNet™, 5-pole halogen-free, shielded, free cable end, to Elbowed Female M12, coding: A SPEEDCON, cable length: 5 m, Unshielded plug-in connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1419035

Packing unit 1 pc

Catalog page Page 431 (C-2-2017)

GTIN 4046356542784

Weight per Piece (excluding packing) 310.500 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 5 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 5

Color handle area black

Coding A - standard

Signal type/category CANopen®

DeviceNet™

Status display No

Overvoltage category II

Degree of pollution 3

Torque 0.4 Nm (M12 connector)

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU

Material, knurls Zinc die-cast, nickel-plated

Pin assignment

Contact | Color (signal designation) | Contact (optional) 1 (Socket) | SR (shield)

2 (Socket) | RD (V+)

3 (Socket) | BK (V-)

4 (Socket) | WH (CAN_H)

5 (Socket) | BU (CAN_L)

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type CAN Bus/DeviceNet drop cable

Cable type (abbreviation) 923

UL AWM style 21198 (80°C/300 V)

Cable structure 2xAWG24/19+2xAWG22/19

Conductor cross section 2x 0.25 mm² (Data cable)

2x 0.34 mm² (Power supply)

1x 0.34 mm² (Drain wire)

AWG signal line 24

AWG power supply 22

Conductor structure signal line 19x 0.13 mm

Conductor structure, voltage s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-5,0-923/FR CAN SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.