

INDUSTRIAL COMPONENT DATA

SAC-5PY-F/2X 0,5-920-MS-FS 1436026 PHOENIX CONTACT

Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5PY-F/2X 0,5-920-MS-FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5PY-F/2X 0,5-920-MS-FS
Catalog number	1436026
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-D77AE9165B
Generated	2026-08-04

Product Overview

Bus system cable

Bus System Cable, CANopen®, DeviceNet™, 5-pole halogen-free, shielded, Straight female M12, coding: A SPEEDCON, to Straight female M12, coding: A SPEEDCON and Straight connector M12, coding: A SPEEDCON, cable length: 0.5 m, all pluggable connectors unshielded, Display is positioned above pin 1

Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, Socket straight M12 SPEEDCON, coding: A, on Socket straight M12 SPEEDCON, coding: A and Plug straight M12 SPEEDCON, coding: A, cable length: 0.5 m, all connectors unshielded, Shield connected to pin 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Application Standard

Sensor type CANopen®

Number of positions 5

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

InterfacesBus system CANopen®/DeviceNet™

Signal type/category CANopen®

DeviceNet™

SignalingStatus display no

Status display present No

Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$

Nominal voltage UN 48 V AC

60 V DC

Nominal current IN 4 A

Transmission medium Copper

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material for screw connection Zinc die-cast, nickel-plated

DimensionsDimensional drawing

Center distance 21 mm

Connection dataPin assignment

Contact Color (signal designation) Contact (optional) 1 (Distributor) SR (shield) 1 (Plug) 1 (Socket)

2 (Distributor) RD (V+) 2 (Plug) 2 (Socket)

3 (Distributor) BK (V-) 3 (Plug) 3 (Socket)

4 (Distributor) WH (CAN_H) 4 (Plug) 4 (Socket)

5 (Distributor) BU (CAN_L) 5 (Plug) 5 (Socket)

ConnectorConnection 1

Type Socket straight M12 SPEEDCON

Number of positions 5

Locking type SPEEDCON

Coding type A (Standard)

Ambient temperature (operation) $-25 \text{ }^{\circ}\text{C} \dots 90 \text{ }^{\circ}\text{C}$

Connection 2

Type Socket straight M12 SPEEDCON

Number of positions 5

Locking type SPEEDCON

Coding type A (Standard)

Ambient temperature (operati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5PY-F/2X 0,5-920-MS-FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.