

INDUSTRIAL COMPONENT DATA

SAC-4P-10,0-990/M12FS 1558386 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-10,0-990/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-10,0-990/M12FS
Catalog number	1558386
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-389AF3C2B1
Generated	2026-08-04

Product Overview

Bus system cable

Bus system cable, CC-Link (10 MBit/s), 4-pole, shielded, free cable end, a Straight female M12, encoding: A, cable length: 10 m

Bus system cable, CC link (10 Mbps), 4-position, PVC, red, shielded, free cable end, on Socket straight M12, coding: A, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Application Standard

Sensor type CC link

Number of positions 4

No. of cable outlets 1

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

InterfacesSignal type/category CC link, 10 Mbps

SignalingStatus display no

Status display present No

Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$

Nominal voltage UN 48 V AC

60 V DC

Nominal current IN 4 A

Transmission medium Copper

Mechanical propertiesMechanical data

Insertion/withdrawal cycles ≥ 100

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material for screw connection Zinc die-cast, nickel-plated

Connection dataPin assignment

Contact Color (signal designation) Contact (optional) 1 (Socket) SR (shield)

2 (Socket) WH (DB)

3 (Socket) YE (DG)

4 (Socket) BU (DA)

ConnectorConnection 1

Type free cable end

Connection 2

Type free cable end

Cable/lineCable length 10 m

CC-Link [990]

Cable weight 78.8 kg/km

Number of positions 3

Shielded yes

Cable type CC-Link [990]

Conductor structure 3xAWG20/7 + 1xAWG22/19 (filler litz wire)

Conductor structure signal line 7x 0.28 mm

AWG signal line 20

Conductor cross section 0.5 mm²

External cable diameter 7.70 mm

Outer sheath, material PVC

External sheath, color red

Conductor material Bare Cu litz wires

Material wire i...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-10,0-990/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.