

INDUSTRIAL COMPONENT DATA

NBC-M12MSD/ 2,0-93B CMC 1524307 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSD/ 2,0-93B CMC



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSD/ 2,0-93B CMC
Catalog number	1524307
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-2E9A9DCB1D
Generated	2026-07-29

Product Overview

Bus system cable

Network cable, PROFINET CAT5 (100 MBit/s), EtherCAT® CAT5 (100 MBit/s), 4-pole, shielded (Advanced Shielding Technology), Straight M12 connector, coding: D/IP67, to free cable end, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1524307

Packing unit 1 pc

Catalog page Page 264 (AX-2011)

GTIN 4046356021388

Weight per Piece (excluding packing) 148.450 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 2 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

General

Note This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 8.2 Connectors for Outside Environment (Balanced cabling)

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding D - data

Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Material

Flammability rating according to UL 94 V0

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material PA 6.6

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Standards and Regulations

Flammability rating according to UL 94 V0

Cable

Cable type PROFINET PVC stranded CAT5

Cable type (abbreviation) 93B

Cable abbreviation 2YY(ST)CY

UL AWM style 21694

Cable structure 1x4xAWG22/7; SF/TQ

Conductor cross section 4x 0.34 mm²

AWG signal line 22

Conductor structure signal line 7x 0.25 mm

Core diameter....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSD/ 2,0-93B CMC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.