

INDUSTRIAL COMPONENT DATA

SAC-5P- 5,0-920/M12FS 1507489 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-5,0-920/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-5,0-920/M12FS
Catalog number	1507489
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-A117DA2F34
Generated	2026-07-31

Product Overview

Bus system cable

Bus System Cable, CANopen®, DeviceNet™, 5-pole halogen-free, shielded, free cable end, to Straight female M12, encoding: A, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1507489

Packing unit 1 pc

Catalog page Page 433 (C-2-2017)

GTIN 4017918900281

Weight per Piece (excluding packing) 310.700 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 5 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

General

Note Further products with variable cable lengths can be found in the accessories section

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 5

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Signal type/category CANopen®

DeviceNet™

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Torque 0.4 Nm (M12 connector)

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Pin assignment

Contact | Color (signal designation) | Contact (optional) 1 (Socket) | SR (shield)

2 (Socket) | RD (V+)

3 (Socket) | BK (V-)

4 (Socket) | WH (CAN_H)

5 (Socket) | BU (CAN_L)

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type CAN Bus/DeviceNet

Cable type (abbreviation) 920

UL AWM style 21198 (80°C/300 V)

Cable structure 2xAWG24/19+2xAWG22/19

Conductor cross section 2x 0.25 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-5,0-920/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.