

INDUSTRIAL COMPONENT DATA

SAC-5PY-M/2X 5,0-920 1436097 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5PY-M/2X 5,0-920



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5PY-M/2X 5,0-920
Catalog number	1436097
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-300813995F
Generated	2026-07-31

Product Overview

Bus system cable

Bus system cable, CANopen®, DeviceNet™, 5-pole halogen-free, shielded, Straight M12 connector, coding: A SPEEDCON, to free cable end and free cable end, cable length: 5 m, Unshielded plug-in connector, The display is placed above pin 1

Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, Plug straight M12 SPEEDCON, coding: A, on free cable end and free cable end, cable length: 5 m, Connector unshielded, Shield connected to pin 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Application Standard

Sensor type CANopen®

Number of positions 5

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

InterfacesBus system CANopen®/DeviceNet™
Signal type/category CANopen®
DeviceNet™
SignalingStatus display no
Status display present No
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Transmission medium Copper
Material specificationsFlammability rating according to UL 94 HB
Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
DimensionsDimensional drawing
Center distance 21 mm
Connection dataPin assignment
Contact Color (signal designation) Contact (optional) 1 (Distributor) SR (shield)
2 (Distributor) RD (V+)
3 (Distributor) BK (V-)
4 (Distributor) WH (CAN_H)
5 (Distributor) BU (CAN_L)
ConnectorConnection 1
Type Plug straight M12 SPEEDCON
Number of positions 5
Locking type SPEEDCON
Coding type A (Standard)
Ambient temperature (operation) -25 °C ... 90 °C
Connection 2
Type free cable end
Connection 3
Type free cable end
Cable/lineCable length 5 m
CANopen®/DeviceNet™, PUR, violet [920]
Dimensional drawing
Cable weight 90 kg/km
UL AWM Style 21198 (80°C/300 V)
Number of positions 4
Shielded yes
Cable type CANopen®/DeviceNet™, PUR, violet [9...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5PY-M/2X 5,0-920 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.