

INDUSTRIAL COMPONENT DATA

SACC-DSI-M12FSD-4P-M16XL/0,5 1411585 PHOENIX CONTACT Bus system flat-type plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12FSD-4P-M16XL/0,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12FSD-4P-M16XL/0,5
Catalog number	1411585
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-25E55487AE
Generated	2026-08-01

Product Overview

Bus system flat-type plug

Conect. plug. to be apar. wall poster., PROFINET CAT5 (IEC11801:2002), 4-pole, Built-in mounting female, straight, M12-Standard, D, to free cable end, Rear mounting, M16 x 1.5, Single stranded wires, cable length: 0.5 m, 0.34 mm², TPE braided wire, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) 1238884

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1411585

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 45 (C-2-2017)

GTIN 4046356935814

Weight per Piece (excluding packing) 25.700 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length of cable 0.5 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 8.2 Connectors for Outside Environment (Balanced cabling)

Rated current at 40°C 4 A

Rated voltage 250 V

Rated surge voltage 2.5 kV

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding D - data

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Individual wires

Insertion/withdrawal cycles > 100

Torque 0.8 Nm ... 1.3 Nm (Installation-side)

Mounting type Rear mounting M16 x 1.5 With flat nut

Assembly instructions Tightening limitation

Material

Flammability rating according to UL 94 V0

Contact material CuZn

C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12FSD-4P-M16XL/0,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.