

INDUSTRIAL COMPONENT DATA

QPD W 4X2,5 9-14 M25 FC GY 1582316 PHOENIX CONTACT

Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: QPD W 4X2,5 9-14 M25 FC GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	QPD W 4X2,5 9-14 M25 FC GY
Catalog number	1582316
Category	Sensor-actuator connector chassis
Minimum order	1 Pcs
Document ID	EO-DE1AB7F4A3
Generated	2026-08-05

Product Overview

Panel feed-through

Feedthrough, QUICKON connection, number of poles: 4, 1 mm² ... 2.5 mm², 690 V, 20 A, grey, with QUICKON nut, cable diameter range: 9 mm ... 14 mm and 9 mm... 14 mm, mounting thread: M25, Flat plug connection, 2.5 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1582316

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 98 (PC-2011)

GTIN 4046356463478

Weight per Piece (excluding packing) 35.700 g

Custom tariff number 85366990

Country of origin DE (Germany)

General

Type QPD 4x2,5

Color gray

Locking type Screw locking

Connection method QUICKON connection

IDC connection

Number of positions 4

Note number of positions 4

Wrench size, union nut 22 mm

Tightening torque, union nut 5 Nm

Tightening torque, counter nut 5 Nm

Wrench size, counter nut 27 mm

Number of connections 10

Conductor cross section flexible min. 1 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section solid min. 1 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section AWG min. 16

Conductor cross section AWG max. 14

Dimensions of slip-on connection 4.8 x 0.8 mm

Cable

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter VDE 0295 class 1 to 6/min. 0.15 mm

Wire insulation material PVC/PE/TPE/rubber

Wire diameter including insulation 2 mm ... 3.8 mm

External cable diameter 9 mm ... 14 mm

9 mm ... 14 mm

Conductor cross section 2.5 mm²

Position marking 1, 2, 3, 4

Ambient conditions

Degree of protection IP66

IP68 (2 m / 24 h)

IP69K

Ambient temperature (operation) -40 °C ... 100 °C

Ambient temperature (storage/transport) -40 °C ... 100 °C

Temperature when conductor connected -5 °C ... 50 °C

Electrical characteristics

Nominal current I_N 20 A

Rated current 20 A

Rated voltage (II...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QPD W 4X2,5 9-14 M25 FC GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.