

INDUSTRIAL COMPONENT DATA

C PX A 405X305X202 0899333 PHOENIX CONTACT Junction box

Brand: PHOENIX CONTACT | Manufacturer Part Number: C PX A 405X305X202



Manufacturer	PHOENIX CONTACT
MPN / Reference	C PX A 405X305X202
Catalog number	0899333
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-3798A26CB8
Generated	2026-08-05

Product Overview

Junction box

Empty housing, material: Fiberglass reinforced polyester, with graphite supplement, black, 305 mm x 405 mm x 202 mm, type of closure: Door, scope of delivery - ATD: Hinge for door with 8 mm square closure, Hinge for door with 8 mm square closure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

Key Commercial Data

Orderkey 0899333

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 534 (C-3-2017)

GTIN 4055626276021

Weight per Piece (excluding packing) 99.990 g

Custom tariff number 85389099

Country of origin HU (Hungary)

General

Type Ex empty enclosure with door

Note Mounting plate required

Scope of supply Door hinge with 8 mm square lock

Color black

Flammability rating according to UL 94 V0

Direct DIN rail mounting No

Useable DIN rail type NS 35

Dimensions

Width 305 mm

Height 405 mm

Depth 202 mm

Clearance width, maximum DIN rail length 365 mm

Assembly length, max. 345 mm

General

Housing material Glass-fiber-reinforced polyester with added graphite

Cover fastening Door

Note Square lock

Fixing device External fixing clips

External fixing clip not supplied as standard

Seal material Silicon

Components halogen-free

Ambient conditions

Degree of protection of housing (IP) IP66

Protection class II

Degree of protection (IK) 7.00 J EN 60079-0

Temperature in operating conditions -55 °C ... 127 °C

Standards and Regulations

Standards/regulations EN 60079-0

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 10.0.127180190eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027141137eCl@ss 5.127180100eCl@ss

6.027180100eCl@ss 7.027180190eCl@ss 8.027180190eCl@ss 9.027180190

ETIM 3.0EC000897ETIM 4.0EC002498ETIM 5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C PX A 405X305X202 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.