

INDUSTRIAL COMPONENT DATA

C1 S4 A 260X380X160 0899594 PHOENIX CONTACT Junction box

Brand: PHOENIX CONTACT | Manufacturer Part Number: C1 S4 A 260X380X160



Manufacturer	PHOENIX CONTACT
MPN / Reference	C1 S4 A 260X380X160
Catalog number	0899594
Category	Enclosure/switchgear cabinet (empty)
Minimum order	2 Pcs
Document ID	EO-AFE7C450C8
Generated	2026-08-06

Product Overview

Junction box

Terminal box, equipped with flange plates below, material: Stainless steel 304 / 1.4301, surface resistance: brushed, silver, 260 mm x 380 mm x 160 mm, type of closure: Door with changeable hinge, scope of delivery - ATD: Door hinge with rotating closure with quarter turn, Mounting plate, Double bit key, Fixing bracket with mounting screws, M12 grounding bolt placed on the outside, Installation instructions, Door hinge with twist lock with quarter turn

Junction box, With flange plate fixing, below, material: Stainless steel 304 / 1.4301, surface resistance: brushed, silver, 260 mm x 380 mm x 160 mm, type of locking: Door with replaceable hinge, scope of supply - ATD: Door hinge with quarter turn locking, Mounting panel, Double-bit key, Fixing angle with mounting screws, M12 grounding bolts, affixed externally, Installation notes, Door hinge with quarter turn locking

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Terminal box

Scope of delivery Door hinge with quarter turn locking

Mounting panel

Double-bit key

Fixing angle with mounting screws

M12 grounding bolts, affixed externally

Installation notes

Flange plates

Type 30

Data management status

Article revision 01

Insulation characteristics

Protection class I

Electrical propertiesMaximum power dissipation 16 W (T6 up to 40 °C)

10 W (T6 up to 55 °C)

6 W (T6 up to 65 °C)

22 W (T5 up to 40 °C)

16 W (T5 up to 55 °C)

12 W (T5 up to 65 °C)

26 W (T4 up to 40 °C)

12.5 W (T4 up to 55 °C)

16 W (T4 up to 65 °C)

DimensionsDimensional drawing

Width 260 mm

Height 380 mm

Depth 160 mm

Clearance width, maximum DIN rail length 204 mm

Max. material thickness 1.5 mm

Material specificationsColor silver

Material Stainless steel 304 / 1.4301

Seal material Silicon

Surface characteristics brushed

Note 240 grain

Mechanical propertiesGeneral

Type of locking (GRP) Door with replaceable hinge Quarter turn locking with two-way key bit

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -55 °C ... 135 °C

MountingAssembly note External fixing clips

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C1 S4 A 260X380X160 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.