

INDUSTRIAL COMPONENT DATA

CA-12P1N126L00 1624050 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-12P1N126L00



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-12P1N126L00
Catalog number	1624050
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-DDEF70E71F
Generated	2026-08-04

Product Overview

Device connector, front mounting

M23, Conect. plug. to be apar. front wall, AC, straight, shielded: yes, for standard lock and SPEEDCON, No. of poles: 12, Direction of rotation: Standard, contact type: Male, Weld connection, Axial joint, Central fixing M20 x 1.5, positionable by lock nut, coding:N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1624050

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 90 (C-2-2017)

GTIN 4055626227719

Weight per Piece (excluding packing) 42.200 g

Custom tariff number 85366990

Country of origin DE (Germany)

Data of the insulating body

Coding N

Insulator material PBT

Contact material CuZn
Contact surface material Ni/Au
Insertion/withdrawal cycles mechanical 100
Contact connection method Solder connection
Type of contacts Pin
Application Signal
Number of positions 12
Contact diameter of signal contacts 1 mm
Litz wire cross section of signal contacts max. 1 mm²
Nominal current per signal contact at 25°C 8 A
Nominal voltage, signal contact 150 V
Rated surge voltage 1.5 kV
Overvoltage category II
Degree of pollution 3
Housing data
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking for standard and SPEEDCON interlock
Degree of protection (when plugged in) IP67/IP69K
Thread type M23
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440102eCl@ss 8.027440102eCl@ss 9.027440103
ETIM 5.0EC002635ETIM 6.0EC002061
UNSPSC 13.239121413
ETIM for 1624050 Connectors (EC003569)
Feature Name
Feature Value
With shield connection (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-12P1N126L00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.