

INDUSTRIAL COMPONENT DATA

CA-16S1N126Y00 1619861 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-16S1N126Y00



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-16S1N126Y00
Catalog number	1619861
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-4860010352
Generated	2026-08-04

Product Overview

Device connector, front mounting

M23, Conect. plug. to be apar. front wall, AC, straight, shielded: yes, for standard lock and SPEEDCON, No. of poles: 16, Direction of rotation: Standard, contact type: Female, Weld connection, Axial joint, Central fixing M20 x 1.5, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1243860

M23, Device connector front mounting, series: CA, straight, shielded: yes, for standard and SPEEDCON interlock, No. of pos.: 16, Direction of rotation: Standard, contact connection type: Socket, Solder connection, Axial seal, Central fastening M20 x 1.5, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Circular connectors (device side)

Data management status

Article revision 05

ConnectorInsulating body

Coding N

Insulation body material PBT

Contact material CuZn

Contact surface material Ni/Au

Insertion/withdrawal cycles 100

Connection method Solder connection
Contact switching type Socket
Application Signal
Number of positions 16
Direction of rotation Standard
Connection profile 16
Rated voltage 48 V AC
74 V DC
Rated surge voltage 1.5 kV
Overvoltage category III
Degree of pollution 3
Contact diameterSignal contacts 1 mm
Litz wire cross-sectionSignal contactsmax. 1 mm²
Nominal current per signal contact 8 A
Housing
Order information: If necessary, order locking nut separately
Housing material GD-Zn
Type of locking for standard and SPEEDCON interlock
Pg screw connection none
Degree of protection (plugged in) IP67
Thread type M23
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -40 °C ... 125 °C
ETIM for 1619861 Connectors (EC002635)
Feature Name
Feature Value
Number of data contacts (EF012232)
0
Number of power contacts (EF012216)
0
Ambient temperature (EF002386)
-40 °C
Type of locking (EF000208)
Other
With protective conductor (EF007468)
No
Screened (EF000881)
No
With status indication (EF001602)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-16S1N126Y00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.