

INDUSTRIAL COMPONENT DATA

CA-19S1N1280DUS 1624335 PHOENIX CONTACT Cable connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-19S1N1280DUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-19S1N1280DUS
Catalog number	1624335
Category	Sensor-actuator connector chassis
Minimum order	1 Pcs
Document ID	EO-1BA7A7F8A0
Generated	2026-08-02

Product Overview

Cable connector

M23, Plug connector. for cables, AC, straight, shielded: yes, SPEEDCON lock, No. of poles: 16+3, Direction of rotation: Standard, type of contact: Female, Solder connection, Cable diameter range: 3 mm ... 14.5 mm, coding:N, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1245141

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1624335

Packing unit 1

GTIN 4055626263380

Custom tariff number 85366990

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 6.027279200eCl@ss 7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 5.0EC002061ETIM 6.0EC002061

UNSPSC 13.239121413

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-19S1N1280DUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.