

INDUSTRIAL COMPONENT DATA

CA-1RS1N8A0000 1623626 PHOENIX CONTACT Insert contacts, number of poles: 16+2+PE, type of contact: Socket, C..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-1RS1N8A0000



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-1RS1N8A0000
Catalog number	1623626
Category	Contact insert for circular connectors
Minimum order	10 Pcs
Document ID	EO-F26B465224
Generated	2026-08-05

Product Overview

Insert contacts, number of poles: 16+2+PE, type of contact: Socket, Connection set
Contact insert, M23, number of poles: 16+2+FE, contact type: Female, Crimped connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Insert contacts, number of poles: 16+2+PE, type of contact: Socket, Connection set

Data commercial

Key order One million six hundred twenty three thousand six hundred twenty six

Packing unit 10 pcs

Key selling ABRBFY -

Minimum order quantity 10 pcs

EAN Four trillion fifty five billion six hundred twenty six million one hundred seventy thousand five hundred eighty nine

Unit weight (excluding packaging) 2,440 g

Tariff number tariff Eighty five million four hundred seventy two thousand

Country of origin DE (Germany)

Overview

Observation Indication of order: The contacts crimpados 16 x Ø 1 mm, 3 x Ø 1.5 mm, must be ordered separately

Direction of rotation of the numbering of the contact camera Standard

Encoding N

Connection type of contact Connection set

Type of contacts Female

N. ° poles Nineteen

Diameter of contact of the power contacts 1.5 mm

Section min. of braid of contact of power 0.75 mm²

Section max. of braid of contact of power 1 mm²

Rated current per contact power at 25°C 10 To

Diameter of contact of the signal contacts 1 mm

Section min. of braid of signal contacts 0,08 mm²

Section max. wire braided signal contacts 1 mm²

Rated current per contact signal-to-25°C 8 To

Environmental conditions

Room temperature -40 °C ... 125 °C

Data according to DIN en 61984:2001

Rated voltage/of Contacts service power 150 V

Rated voltage transient power Contacts 1.5 kV

Category of surge power Contacts II

Degree of dirt power Contacts Three

Rated voltage/of Contacts service signals 150 V....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-1RS1N8A0000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.