

INDUSTRIAL COMPONENT DATA

CA-1RS1N8A6Y00 1624017 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: CA-1RS1N8A6Y00



Manufacturer	PHOENIX CONTACT
MPN / Reference	CA-1RS1N8A6Y00
Catalog number	1624017
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-25FA8A8438
Generated	2026-08-02

Product Overview

Device connector, front mounting

M23, Conect. plug. to be apar. front wall, AC, straight, shielded: yes, for standard and SPEEDCON locking, No. of poles: 16+2+FE, Direction of rotation: Standard, contact type: Female, Crimped connection, Axial joint, Central fixing M20 x 1.5, coding:N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1624017

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 89 (C-2-2017)

GTIN 4055626228310

Weight per Piece (excluding packing) 22.600 g

Custom tariff number 85366990

Country of origin DE (Germany)

Data of the insulating body

Note Order information: Order crimp contacts 16 x Ø 1 mm, 3 x Ø 1.5 mm separately

Coding N

Insulator material PA 6.6
Contact connection method Crimp connection
Type of contacts Socket
Application Signal
Number of positions 19
Contact diameter of power contacts 1.5 mm
Litz wire cross section of power contacts min. 0.75 mm²
Litz wire cross section of power contacts max. 1 mm²
Nominal current per power contact at 25°C 10 A
Nominal voltage, power contact 150 V
Rated surge voltage 1.5 kV
Overvoltage category II
Degree of pollution 3
Contact diameter of signal contacts 1 mm
Litz wire cross section of signal contacts min. 0.08 mm²
Litz wire cross section of signal contacts max. 1 mm²
Nominal current per signal contact at 25°C 8 A
Nominal voltage, signal contact 150 V
Rated surge voltage 1.5 kV
Overvoltage category II
Degree of pollution 3
Housing data
Note Order information: If necessary, order locking nut separately
Housing material CuZn
Type of locking for standard and SPEEDCON interlock
Degree of protection (when plugged in) IP67
Thread type M23
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufac..."

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CA-1RS1N8A6Y00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.