

## INDUSTRIAL COMPONENT DATA

# CAB-MSTB32/2XMC9/22/18,0M/C3/S 1013239 PHOENIX CONTACT Interface cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: CAB-MSTB32/2XMC9/22/18,0M/C3/S



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | CAB-MSTB32/2XMC9/22/18,0M/C3/S |
| Catalog number  | 1013239                        |
| Category        | PLC connection cable           |
| Minimum order   | 1 Pcs                          |
| Document ID     | EO-D5D7141F8F                  |
| Generated       | 2026-07-29                     |

## Product Overview

Interface cable

16-channel VIP cable for use with Honeywell C300 Universal I/O Module, 22 AWG, 18.0 m length

VIP 16-channel cable for use with Honeywell C300 universal I/O, 22 AWG, 18.0 m long

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; INTERFACE Components (IF)

## Additional Product Information

Technical dataProduct propertiesProduct type System cable  
Product family VIP I/O-Marshalling  
Environmental and real-life conditionsAmbient conditions  
Ambient temperature (operation) -40 °C ... 90 °C (static)  
Ambient temperature (storage/transport) -40 °C ... 90 °C  
Electrical propertiesOperating voltage (AC/DC) <= 30 V AC/DC  
Current (Per path) <= 2 A  
Cable/lineCable length 18 m  
Number of positions 16  
Shielded yes  
Conductor type Assembled shielded round cable  
Conductor structure signal line 7x  
AWG signal line 22

Conductor cross section 16x 0.36 mm<sup>2</sup>  
External cable diameter 8.50 mm  
Conductor material Tin-plated Cu litz wires  
Halogen-free yes  
Flame resistance IEC 60332-1  
Cable type Splitting cable for two modules  
Connection dataField level  
Connection method pluggable  
Number of connections 2  
Number of positions 18  
Pitch 3.81 mm  
Controller level  
Connection method pluggable  
Number of connections 1  
Number of positions 32  
Pitch 5.08 mm

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CAB-MSTB32/2XMC9/22/18,0M/C3/S with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.