

**INDUSTRIAL COMPONENT DATA**

# WT-BASE HF 5 3240702 PHOENIX CONTACT Cable binder base

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-BASE HF 5



|                 |                                                         |
|-----------------|---------------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                         |
| MPN / Reference | WT-BASE HF 5                                            |
| Catalog number  | 3240702                                                 |
| Category        | Accessories/spare parts for universal suspension system |
| Minimum order   | 100 Pcs                                                 |
| Document ID     | EO-7D4B46F896                                           |
| Generated       | 2026-08-01                                              |

## Product Overview

Cable binder base

Cable tie socket for cable ties up to 5 mm wide, screwable, 3.5 mm clamping hole, 2-sided cable tie wall pass-through

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                  |
|--------------|----------------------------------|
| Catalog path | PHOENIX CONTACT > CABINET add-on |
|--------------|----------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 3240702

Packing unit 100 pc

Minimum order quantity 100 pc

Catalog page Page 666 (C-3-2017)

GTIN 4046356703895

Weight per Piece (excluding packing) 0.600 g

Custom tariff number 39269097

Country of origin TW (Taiwan)

Dimensions

Length (b) 15 mm

Width (a) 9.5 mm

Height (c) 7 mm

Hole diameter 3.5 mm

**Ambient conditions**

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (assembly) -10 °C ... 60 °C

**General**

Color transparent

Type Fixing

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA 6.6

Tensile strength 0 N

**Standards and Regulations**

Flammability rating according to UL 94 V2

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

**Classifications**eCl@ss 4.027140702eCl@ss 4.127140702eCl@ss 5.027140702eCl@ss 5.127140700eCl@ss 6.027140700eCl@ss  
7.023159007eCl@ss 8.023159007eCl@ss 9.023159007

ETIM 3.0EC000046ETIM 4.0EC000046ETIM 5.0EC000046ETIM 6.0EC000046

UNSPSC 6.0130212109UNSPSC 7.090127121703UNSPSC 1127121703UNSPSC 12.0127121703UNSPSC  
13.227121703**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send PHOENIX CONTACT / WT-BASE HF 5 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).**GLOBAL OFFICES**Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, DubaiCatalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.