

INDUSTRIAL COMPONENT DATA**WT-HF 12,6X1000 BK 3240729 PHOENIX CONTACT Cable tie**

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-HF 12,6X1000 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	WT-HF 12,6X1000 BK
Catalog number	3240729
Category	Cable tie
Minimum order	50 Pcs
Document ID	EO-222AEF0743
Generated	2026-07-31

Product Overview

Cable tie

Cable fasteners, standard version, for fast and safe grouping

Cable binders for quick and secure bundling, standard version

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Cable tie

Type Internal teeth

Tensile strength GRP 1080 N

DimensionsWidth 12.6 mm

Length 1000 mm

Material specificationsColor black (RAL 9005)

Material PA 6.6

Flammability rating according to UL 94 V2

Components free from silicone and halogen

Cable/lineExternal cable diameter 40 mm ... 302 mm

Tensile strength 1080 N

Environmental and real-life conditionsAmbient conditions

Optimum ambient temperature (storage/transport) 23.00 °C 50.00 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are

ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (assembly) -10 °C ... 60 °C

Resistance to UV radiation no

Short-term temperature 110 °C

Mounting Mounting type Cannot be removed

ETIM for 3240729 Fixings and fasteners (EC000046)

Feature Name

Feature Value

Length belt/tape/tie (EF000063)

1000 mm

Tie thickness (EF004499)

1.95 mm

Operating temperature (EF002393)

-10 °C

Mounting temperature (EF008...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WT-HF 12,6X1000 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.