

## INDUSTRIAL COMPONENT DATA

## WT-HF 4,5X200 BK-L 3240762 PHOENIX CONTACT Cable tie

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-HF 4,5X200 BK-L



|                 |                    |
|-----------------|--------------------|
| Manufacturer    | PHOENIX CONTACT    |
| MPN / Reference | WT-HF 4,5X200 BK-L |
| Catalog number  | 3240762            |
| Category        | Cable tie          |
| Minimum order   | 1000 Pcs           |
| Document ID     | EO-8BC11E2BD6      |
| Generated       | 2026-07-31         |

## Product Overview

Cable tie

Cable fasteners, standard version, for fast and safe grouping

Cable tie, standard version, for quick and secure banding

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |                                  |
|--------------|----------------------------------|
| Catalog path | PHOENIX CONTACT > CABINET add-on |
|--------------|----------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 3240762

Packing unit 1000 pc

Minimum order quantity 1000 pc

Note Made to Order (non-returnable)

Catalog page Page 659 (C-3-2017)

GTIN 4046356704809

Weight per Piece (excluding packing) 1.340 g

Custom tariff number 39269097

Country of origin IT (Italy)

Dimensions

Length (b) 200 mm

Width (a) 4.8 mm

Cable diameter 3 mm ... 50 mm

**Ambient conditions**

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (assembly) -10 °C ... 60 °C

Optimum ambient temperature (storage/transport) 23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.

Short-term temperature 110 °C

**General**

Color black

Type Internal teeth

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA 6.6

Tensile strength 220 N

Standards and Regulations

Resistance to UV radiation no

Connection in acc. with standard UL

Flammability rating according to UL 94 V2

Environmental Product Compliance

China R...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / WT-HF 4,5X200 BK-L with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.