

INDUSTRIAL COMPONENT DATA

WT-HF 7,8X540 BK 3240721 PHOENIX CONTACT Cable tie

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-HF 7,8X540 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	WT-HF 7,8X540 BK
Catalog number	3240721
Category	Cable tie
Minimum order	100 Pcs
Document ID	EO-9F9EA84F29
Generated	2026-07-29

Product Overview

Cable tie

Cable fasteners, standard version, for fast and safe grouping

Cable tie, standard version, for quick and secure banding

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 3240721

Packing unit 100 pc

Minimum order quantity 100 pc

Catalog page Page 659 (C-3-2017)

GTIN 4046356704373

Weight per Piece (excluding packing) 7.430 g

Custom tariff number 39269097

Country of origin IT (Italy)

Dimensions

Length (b) 540 mm

Width (a) 7.8 mm

Cable diameter 4 mm ... 158 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (assembly) -10 °C ... 60 °C

Optimum ambient temperature (storage/transport) 23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.

Short-term temperature 110 °C

General

Color black

Type Internal teeth

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA 6.6

Tensile strength 540 N

Standards and Regulations

Resistance to UV radiation no

Connection in acc. with standard UL

Flammability rating according to UL 94 V2

Environmental Product Compliance

China RoHS Environmentally friendly use peri...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WT-HF 7,8X540 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.