

## INDUSTRIAL COMPONENT DATA

## WT-HF 9X780 3240778 PHOENIX CONTACT Cable tie

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-HF 9X780



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | PHOENIX CONTACT |
| MPN / Reference | WT-HF 9X780     |
| Catalog number  | 3240778         |
| Category        | Cable tie       |
| Minimum order   | 100 Pcs         |
| Document ID     | EO-305F1E85EC   |
| Generated       | 2026-07-29      |

## Product Overview

Cable tie

Cable fasteners, standard version, for fast and safe grouping

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path PHOENIX CONTACT &gt; CABINET add-on

## Additional Product Information

Key Commercial Data

Orderkey 3240778

Packing unit 100 pc

Minimum order quantity 100 pc

Catalog page Page 658 (C-3-2017)

GTIN 4046356704960

Weight per Piece (excluding packing) 13.000 g

Custom tariff number 39269097

Country of origin IT (Italy)

Dimensions

Length (b) 780 mm

Width (a) 9 mm

Cable diameter 32 mm ... 233 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (assembly) -10 °C ... 60 °C

Optimum ambient temperature (storage/transport) 23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.

Short-term temperature 110 °C

General

Color transparent

Type Internal teeth

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA 6.6

Tensile strength 700 N

Standards and Regulations

Resistance to UV radiation no

Connection in acc. with standard UL

Flammability rating according to UL 94 V2

Environmental Product Compliance

China RoHS Environmentally friendly us...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WT-HF 9X780 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.