

INDUSTRIAL COMPONENT DATA

WT-HT HF 3,6X140 BK 3240783 PHOENIX CONTACT Cable tie

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-HT HF 3,6X140 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	WT-HT HF 3,6X140 BK
Catalog number	3240783
Category	Cable tie
Minimum order	100 Pcs
Document ID	EO-DA92069713
Generated	2026-08-02

Product Overview

Cable tie

Thermoset cable ties up to 125 °C (short-term up to 145 °C) for fast and safe bundling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3240783

Packing unit 100 pc

Minimum order quantity 100 pc

Catalog page Page 661 (C-3-2017)

GTIN 4046356705011

Weight per Piece (excluding packing) 0.650 g

Custom tariff number 39269097

Country of origin HR (Croatia)

Dimensions

Length (b) 140 mm

Width (a) 3.6 mm

Cable diameter 2 mm ... 35 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 125 °C

Ambient temperature (assembly) -10 °C ... 60 °C

Optimum ambient temperature (storage/transport) 23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.

Short-term temperature 145 °C

General

Color black

Type Internal teeth

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA 6.6

Tensile strength 130 N

Standards and Regulations

Flammability rating according to UL 94 V2

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold v...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WT-HT HF 3,6X140 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.