

INDUSTRIAL COMPONENT DATA

WT-HT HF 7,8X365 BK 3240793 PHOENIX CONTACT Cable tie

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-HT HF 7,8X365 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	WT-HT HF 7,8X365 BK
Catalog number	3240793
Category	Cable tie
Minimum order	100 Pcs
Document ID	EO-535CC7E6D9
Generated	2026-08-02

Product Overview

Cable tie

Thermoset cable ties up to 125 °C (short-term up to 145 °C) for fast and safe bundling

Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Cable tie

Type Internal teeth

Tensile strength GRP 540 N

DimensionsWidth 7.8 mm

Length 365 mm

Material specificationsColor black (RAL 9005)

Material PA 6.6

Flammability rating according to UL 94 V2

Components free from silicone and halogen

Cable/lineExternal cable diameter 8 mm ... 100 mm

Tensile strength 540 N

Environmental and real-life conditionsAmbient conditions

Optimum ambient temperature (storage/transport) 23.00 °C 50.00 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are

ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.

Ambient temperature (operation) -40 °C ... 125 °C

Ambient temperature (assembly) -10 °C ... 60 °C

Resistance to UV radiation no

Short-term temperature 145 °C

Mounting type Cannot be removed

ETIM for 3240793 Fixings and fasteners (EC000046)

Feature Name

Feature Value

Length belt/tape/tie (EF000063)

365 mm

Tie thickness (EF004499)

1.8 mm

Operating temperature (EF002393)

-10 °C

Mounting temperature (EF008326)

~...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WT-HT HF 7,8X365 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.