

INDUSTRIAL COMPONENT DATA

WT-E HF 4,8X200 3240720 PHOENIX CONTACT Cable tie

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-E HF 4,8X200



Manufacturer	PHOENIX CONTACT
MPN / Reference	WT-E HF 4,8X200
Catalog number	3240720
Category	Cable tie
Minimum order	100 Pcs
Document ID	EO-E117926B07
Generated	2026-07-27

Product Overview

Cable tie

Cable holders with clamping button for screwing or riveting, perfect for long-lasting fixation almost in any subsoil

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3240720

Packing unit 100 pc

Minimum order quantity 100 pc

Catalog page Page 662 (C-3-2017)

GTIN 4046356704366

Weight per Piece (excluding packing) 1.620 g

Custom tariff number 39269097

Country of origin TW (Taiwan)

Dimensions

Length (b) 200 mm

Width (a) 4.8 mm

Hole diameter 5.2 mm

Cable diameter 3.5 mm ... 44 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (assembly) -10 °C ... 60 °C

Optimum ambient temperature (storage/transport) 23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.

Short-term temperature 110 °C

General

Color transparent

Type Internal teeth

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA 6.6

Tensile strength 220 N

Standards and Regulations

Resistance to UV radiation no

Flammability rating according to UL 94 V2

Environmental Product Compliance

China RoHS Environmentally friendly use period: unl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WT-E HF 4,8X200 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.