

INDUSTRIAL COMPONENT DATA

WT-STEEL SH 4,6X1067 3240818 PHOENIX CONTACT Cable tie

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-STEEL SH 4,6X1067



Manufacturer	PHOENIX CONTACT
MPN / Reference	WT-STEEL SH 4,6X1067
Catalog number	3240818
Category	Cable tie
Minimum order	100 Pcs
Document ID	EO-C147796BA2
Generated	2026-08-03

Product Overview

Cable tie

Cable ties made of stainless steel (AISI 316), also suitable for aggressive environmental conditions (among others: salt water), for fast and safe grouping and fixing

Cable binders, made from rust-free stainless steel (AISI 316), suitable for the harshest of ambient conditions (for example, salt water), with ball lock, for quick and secure bundling and fastening

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Cable tie

Type Steel strip

Tensile strength GRP 890 N

DimensionsWidth 4.6 mm

Length 1067 mm

Max. material thickness 0.25 mm

Material specificationsColor silver-colored

Material Stainless steel 1.4401/AISI 316

Components free from silicone and halogen

Cable/lineExternal cable diameter <= 305.00 mm

Tensile strength 890 N

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -80 °C ... 538 °C

Ambient temperature (assembly) -80 °C ... 538 °C

Resistance to UV radiation yes

MountingMounting type Cannot be removed

ETIM for 3240818 Fixings and fasteners (EC000046)

Feature Name

Feature Value

Length belt/tape/tie (EF000063)

1067 mm

Tie thickness (EF004499)

0.26 mm

Operating temperature (EF002393)

-80 °C

Mounting temperature (EF008326)

-80 °C

Band closure (EF007673)

Ball latch

Material quality (EF001257)

Other

Surface protection (EF000139)

Untreated

UV-stable according to ASTM D6779 (EF008099)

No

Halogen free (EF000025)

Yes

Colour (EF000007)

Silver

Transparent (EF006243)

No

Text strip (EF000129)

None

Releasable closure (EF004907)

No

Type of fastening (EF002442)

None

VG approval (EF008107)

No

MIL approval (EF007933)

Yes

UL approval (EF008093)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WT-STEEL SH 4,6X1067 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.