

## INDUSTRIAL COMPONENT DATA

## WT-STEEL SH 4,6X259 3240822 PHOENIX CONTACT Cable tie

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-STEEL SH 4,6X259



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | WT-STEEL SH 4,6X259 |
| Catalog number  | 3240822             |
| Category        | Cable tie           |
| Minimum order   | 100 Pcs             |
| Document ID     | EO-5C40A52C3F       |
| Generated       | 2026-08-01          |

## Product Overview

## Cable tie

Cable ties made of stainless steel (AISI 316), also suitable for aggressive environmental conditions (among others: salt water), for fast and safe grouping and fixing

Cable binders, made from rust-free stainless steel (AISI 316), suitable for the harshest of ambient conditions (for example, salt water), with ball lock, for quick and secure bundling and fastening

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path PHOENIX CONTACT &gt; CABINET add-on

## Additional Product Information

Technical dataProduct propertiesProduct type Cable tie

Type Steel strip

Tensile strength GRP 890 N

DimensionsWidth 4.6 mm

Length 259 mm

Max. material thickness 0.25 mm

Material specificationsColor silver-colored

Material Stainless steel 1.4401/AISI 316

Components free from silicone and halogen

Cable/lineExternal cable diameter &lt;= 69.00 mm

Tensile strength 890 N

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -80 °C ... 538 °C  
Ambient temperature (assembly) -80 °C ... 538 °C  
Resistance to UV radiation yes  
MountingMounting type Cannot be removed  
ETIM for 3240822 Fixings and fasteners (EC000046)  
Feature Name  
Feature Value  
Length belt/tape/tie (EF000063)  
259 mm  
Tie thickness (EF004499)  
0.26 mm  
Operating temperature (EF002393)  
-80 °C  
Mounting temperature (EF008326)  
-80 °C  
Band closure (EF007673)  
Ball latch  
Material quality (EF001257)  
Other  
Surface protection (EF000139)  
Untreated  
UV-stable according to ASTM D6779 (EF008099)  
No  
Halogen free (EF000025)  
Yes  
Colour (EF000007)  
Silver  
Transparent (EF006243)  
No  
Text strip (EF000129)  
None  
Releasable closure (EF004907)  
No  
Type of fastening (EF002442)  
None  
VG approval (EF008107)  
No  
MIL approval (EF007933)  
Yes  
UL approval (EF008093)  
No

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WT-STEEL SH 4,6X259 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.