

INDUSTRIAL COMPONENT DATA

WT-STEEL SH 7,9X259 3240827 PHOENIX CONTACT Cable tie

Brand: PHOENIX CONTACT | Manufacturer Part Number: WT-STEEL SH 7,9X259



Manufacturer	PHOENIX CONTACT
MPN / Reference	WT-STEEL SH 7,9X259
Catalog number	3240827
Category	Cable tie
Minimum order	100 Pcs
Document ID	EO-328CFAC5D7
Generated	2026-08-03

Product Overview

Cable tie

Cable ties made of stainless steel (AISI 316), also suitable for aggressive environmental conditions (among others: salt water), for fast and safe grouping and fixing

Cable binders, made from rust-free stainless steel (AISI 316), suitable for the harshest of ambient conditions (for example, salt water), with ball lock, for quick and secure bundling and fastening

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type Cable tie

Type Steel strip

Tensile strength GRP 1335 N

DimensionsWidth 7.9 mm

Length 259 mm

Max. material thickness 0.25 mm

Material specificationsColor silver-colored

Material Stainless steel 1.4401/AISI 316

Components free from silicone and halogen

Cable/lineExternal cable diameter <= 69.00 mm

Tensile strength 1335 N

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -80 °C ... 538 °C
Ambient temperature (assembly) -80 °C ... 538 °C
Resistance to UV radiation yes
MountingMounting type Cannot be removed
ETIM for 3240827 Fixings and fasteners (EC000046)
Feature Name
Feature Value
Length belt/tape/tie (EF000063)
259 mm
Tie thickness (EF004499)
0.26 mm
Operating temperature (EF002393)
-80 °C
Mounting temperature (EF008326)
-80 °C
Band closure (EF007673)
Ball latch
Material quality (EF001257)
Other
Surface protection (EF000139)
Untreated
UV-stable according to ASTM D6779 (EF008099)
No
Halogen free (EF000025)
Yes
Colour (EF000007)
Silver
Transparent (EF006243)
No
Text strip (EF000129)
None
Releasable closure (EF004907)
No
Type of fastening (EF002442)
None
VG approval (EF008107)
No
MIL approval (EF007933)
Yes
UL approval (EF008093)
No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WT-STEEL SH 7,9X259 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.