

INDUSTRIAL COMPONENT DATA

CABLE-D37SUB/B/B/HF/S/ 8,0M 2908521 PHOENIX CONTACT Cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: CABLE-D37SUB/B/B/HF/S/ 8,0M



Manufacturer	PHOENIX CONTACT
MPN / Reference	CABLE-D37SUB/B/B/HF/S/ 8,0M
Catalog number	2908521
Category	PLC connection cable
Minimum order	1 Pcs
Document ID	EO-1EEE746D25
Generated	2026-08-01

Product Overview

Cable

Made-up round cable, shielded and halogen-free; Connection 1: D-SUB connection female (1x 37-poles); Connection 2: D-SUB connection female (1x 37-poles); Cable length: 8 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 2908521

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 593 (C-5-2017)

GTIN 4055626306605

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85444290

Country of origin DE (Germany)

General

Nominal voltage UN 25 V AC

60 V DC

Max. current carrying capacity per path 2 A

Max. conductor resistance $\leq 0.09 \text{ ?/m}$
Length of cable 8 m
Single wire, cross section 0.25 mm^2
Single wire, cross section [AWG] 24
External diameter 11.2 mm
Shielding yes
Tinned copper braided shield
Insertion/withdrawal cycles > 200
Environmental conditions
Ambient temperature (operation) $-20 \text{ }^{\circ}\text{C} \dots 50 \text{ }^{\circ}\text{C}$
Ambient temperature (storage/transport) $-20 \text{ }^{\circ}\text{C} \dots 70 \text{ }^{\circ}\text{C}$
Connector 1
Connection name Field level
Connection method D-SUB socket strip
Screw thread UNC 4-40
Torque 0.2 Nm
Number of connections 1
Number of positions 37
Connector 2
Connection name Controller level
Connection method D-SUB socket strip
Screw thread UNC 4-40
Torque 0.2 Nm
Number of connections 1
Number of positions 37
Supported controller
Controller universal
Standards and Regulations
Standard designation Flame retardancy
Standards/regulations IEC 60332-3-22
DIN VDE 0482-266-2-2
Standard designation Halogen-free
Standards/regulations IEC 60754-1
DIN VDE 0482-267-1
Standard designation Concentration of fumes
Standards/regulations IEC 61034-2
Standard designation Corrosiveness of fumes according
Standards/regulations IEC 60754-2
DIN VDE 0472-813
Environmental Product Compliance
REACH SV...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CABLE-D37SUB/B/B/HF/S/ 8,0M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.