

INDUSTRIAL COMPONENT DATA

WG-D HF 7,6 3241099 PHOENIX CONTACT Cable driller

Brand: PHOENIX CONTACT | Manufacturer Part Number: WG-D HF 7,6



Manufacturer	PHOENIX CONTACT
MPN / Reference	WG-D HF 7,6
Catalog number	3241099
Category	Cable tie
Minimum order	1000 Pcs
Document ID	EO-6AEFB1821C
Generated	2026-08-02

Product Overview

Cable driller

Cable attachment for quick and tool-free bundling of lines and conductors, can be disassembled and used again

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3241099

Packing unit 500 pc

Minimum order quantity 1000 pc

Note Made to Order (non-returnable)

Catalog page Page 667 (C-3-2017)

GTIN 4046356717281

Weight per Piece (excluding packing) 0.310 g

Custom tariff number 39269097

Country of origin TW (Taiwan)

Dimensions

Length (b) 22.9 mm

Width (a) 7.6 mm

Cable diameter 5.1 mm ... 7.6 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 85 °C

Ambient temperature (assembly) -10 °C ... 60 °C

Optimum ambient temperature (storage/transport) 23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.

General

Color transparent

Type Notched strip

Components free from silicone and halogen

Flammability rating according to UL 94 V2

Material PA 6.6

Tensile strength 0 N

Standards and Regulations

Resistance to UV radiation no

Flammability rating according to UL 94 V2

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WG-D HF 7,6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.