

**INDUSTRIAL COMPONENT DATA**

# CD-HF 40X80 3240350 PHOENIX CONTACT Cable duct

Brand: PHOENIX CONTACT | Manufacturer Part Number: CD-HF 40X80



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | PHOENIX CONTACT               |
| MPN / Reference | CD-HF 40X80                   |
| Catalog number  | 3240350                       |
| Category        | Slotted cable trunking system |
| Minimum order   | 16 Pcs                        |
| Document ID     | EO-671A823B16                 |
| Generated       | 2026-07-31                    |

## Product Overview

Cable duct

Wiring channel for installation and installation in control cabinets, light grey, halogen-free, top and bottom, width: 40 mm, height: 80 mm, length: 2000 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                  |
|--------------|----------------------------------|
| Catalog path | PHOENIX CONTACT > CABINET add-on |
|--------------|----------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 3240350

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 623 (C-3-2017)

GTIN 4046356508353

Weight per Piece (excluding packing) 1,050.000 g

Custom tariff number 39259020

Country of origin DE (Germany)

Dimensions

Length (b) 2000 mm

Width (a) 40 mm

Height (c) 80 mm

Diameter 40.00 mm

**Ambient conditions**

Ambient temperature (operation) -40 °C ... 90 °C

**General**

Color light grey RAL 7035

7035

Components halogen-free

Flammability rating according to UL 94 V0

Material PC/ABS

Nominal cross section 2071 mm<sup>2</sup>

**Standards and Regulations**

Halogen-free yes

Connection in acc. with standard CSA

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

**Classifications**

eCl@ss 4.027140602eCl@ss 4.127140602eCl@ss 5.027140602eCl@ss 5.127140600eCl@ss 6.027400700eCl@ss  
7.027400703eCl@ss 8.027400703eCl@ss 9.027400703

ETIM 2.0EC000012ETIM 3.0EC000012ETIM 4.0EC000012ETIM 5.0EC000012ETIM 6.0EC000012

UNSPSC 6.0130101815UNSPSC 7.090130101815UNSPSC 1130101815UNSPSC 12.0130101815UNSPSC  
13.239131712

ETIM for 3240350 Slotted cable trunking (EC000012)

**Feature Name****Feature Value**

Height (EF000040)

80 mm

Width (EF000008)

40 mm

Length (EF001438)

2000 mm

Distance of slots (EF005246)

6.5 mm

Slit width (EF005247)

6 mm

Type of side wall (EF000098)

Slotted

Halogen free (EF000025)

Yes

Self-extinguishing (EF000681)

No

Flexible (EF000083)

No

With cov...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CD-HF 40X80 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.