

INDUSTRIAL COMPONENT DATA

MC-25/27-MULTI-67-PV-LG 1415236 PHOENIX CONTACT

Cable feed-through plates

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC-25/27-MULTI-67-PV-LG



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC-25/27-MULTI-67-PV-LG
Catalog number	1415236
Category	Mounting plate for cable support system
Minimum order	1 Pcs
Document ID	EO-82FC153568
Generated	2026-08-05

Product Overview

Cable feed-through plates

Plates for cable passage, number of conductors: 27, outer diameter of the cable: 4x 5 mm ... 7mm, 4x 8mm... 12mm, 13x 10mm... 14mm, 4x 14mm... 20mm, 2x 20mm... 26 mm, material: galvanized steel sheet (Core), material: TPE-SEBS (Outer material), color: light gray, length: 222 mm, width: 92 mm, height: 29.5 mm

Inlet plates, number of conductors: 27, conductor outer diameter: 4x 5 mm 7 mm, 4x 8 mm ... 12 mm, 13x 10 mm ... 14 mm, 4x 14 mm ... 20 mm, 2x 20 mm ... 26 mm, material: galvanised sheet steel (Core), material: TPE-SEBS (outer material), colour: light grey, length: 222 mm, width: 92 mm, height: 29.5 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1415236

Packing unit 1 pc

Catalog page Page 690 (C-2-2017)

GTIN 4055626039428

Weight per Piece (excluding packing) 225.100 g

Custom tariff number 39269097

Country of origin FI (Finland)

Dimensions

Length 222 mm
Width 92 mm
Height 29.5 mm
Drill hole distance, horizontal 62 mm
Drill hole distance, vertical 194 mm
External cable diameter 13x 10 mm ... 14 mm
4x 8 mm ... 12 mm
2x 20 mm ... 26 mm
4x 5 mm ... 7 mm
4x 8 mm ... 12 mm
Ambient conditions
Degree of protection IP66 (Minimum sheet thickness ≥ 2.5 mm)
IP67 (Minimum sheet thickness ≥ 2.5 mm)
Ambient temperature (operation) -40 °C ... 100 °C
General
No. of conductors 27
Material TPE-SEBS
galvanized sheet steel ()
Flammability rating according to UL 94 V0
Color light gray
Torque 1.5 Nm ... 2 Nm (Mounting screws)
Note incl. mounting screws
Installation instructions M8 mounting screw, torque: 1.5 - 2.0 Nm, SW5 Allen key
The mounting screws included should be used for assembly.
Assembly steps:
1) Fix Multigates with the mounting screws provided (observe torque)
2) Make a hole in the membrane (with a screwdriver) or cut off the tip of the cone
3) Guide the cable through the opening (from the outside). Withdraw the cable approximately 20 mm (to improve strain relief).
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC-25/27-MULTI-67-PV-LG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.