


INDUSTRIAL COMPONENT DATA

MC-3/7-MULTI-67-PV-LG 1415234 PHOENIX CONTACT Cable feed-through plates

Brand: PHOENIX CONTACT | Manufacturer Part Number: MC-3/7-MULTI-67-PV-LG



Manufacturer	PHOENIX CONTACT
MPN / Reference	MC-3/7-MULTI-67-PV-LG
Catalog number	1415234
Category	Mounting plate for cable support system
Minimum order	1 Pcs
Document ID	EO-73CED213FA
Generated	2026-08-05

Product Overview

Cable feed-through plates

Plates for cable passage, number of conductors: 7, outer diameter of the cable: 1x 30 mm ... 60 mm, 4x 10 mm... 14 mm, 2x 24 mm... 54 mm, material: galvanized steel sheet (Core), material: TPE-SEBS (outer material), color: light gray, length: 222 mm, width: 92 mm, height: 43 mm

Cable feed-through plates, no. of conductors: 7, external cable diameter: 1x 30 mm ... 60 mm, 4x 10 mm ... 14 mm, 2x 24 mm ... 54 mm, material: galvanized sheet steel (Core), material: TPE-SEBS (external material), color: light gray, length: 222 mm, width: 92 mm, height: 43 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral incl. mounting screws

General 2 mm thick coated, galvanized sheet steel

Product propertiesProduct type Cable feed-through

No. of conductors 7

Data management status

Article revision 00

Connection dataExternal cable diameter 1x 30 mm ... 60 mm

Tightening torque 1.5 Nm ... 2 Nm (Mounting screws)

DimensionsDimensional drawing

Width 92 mm
Height 43 mm
Length 222 mm
Drill hole distance, horizontal 62 mm
Drill hole distance, vertical 194 mm
Hole diameter 8.5 mm
Material specifications Color light gray (RAL 7035)
Material interior galvanized sheet steel (Core)
Material exterior TPE-SEBS (external material)
Flammability rating according to UL 94 V0
Cable/line External cable diameter 30-60 mm 1x 30 mm ... 60 mm
External cable diameter 10-14 mm 4x 10 mm ... 14 mm
External cable diameter 24-54 mm 2x 24 mm ... 54 mm
Environmental and real-life conditions Ambient conditions
Degree of protection IP66 (Minimum sheet thickness ≥ 2.5 mm)
IP67 (Minimum sheet thickness ≥ 2.5 mm)
Ambient temperature (operation) -40°C ... 100°C
Mounting Assembly note M8 mounting screw, torque: 1.5 - 2.0 Nm, SW5 Allen key
The mounting screws included should be used for assembly.

Assembly steps:

- 1) Fix Multigates with the mounting screws provided (observe torque)
- 2) Make a hole in the membrane (with a screwdriver) or cut off the tip of the cone
- 3) Guide the cable through the opening (from the outside). Withdraw the cable approximately 20 mm (to improve strain relief).

ETIM for 1415234 Ca...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MC-3/7-MULTI-67-PV-LG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.