

INDUSTRIAL COMPONENT DATA

G-INS-PG13,5-S68N-NNES-S 1411173 PHOENIX CONTACT

Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INS-PG13,5-S68N-NNES-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INS-PG13,5-S68N-NNES-S
Catalog number	1411173
Category	Cable gland
Minimum order	5 Pcs
Document ID	EO-6E013BBD65
Generated	2026-08-06

Product Overview

Cable gland

Cable gland, screwed connection material: Brass, nickel-plated, cable outer diameter 6 mm ... 12 mm, shielding: no, connection thread: Pg13.5, colour: silver, with O-ring

Cable glands, screw connection material: Brass, nickel-plated, application: Standard, cable outer diameter 6 mm 12 mm, shielding: no, thread: Pg13.5, color: silver, with O-ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1411173

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 697 (C-2-2017)

GTIN 4046356923071

Weight per Piece (excluding packing) 30.860 g

Custom tariff number 74199990

Country of origin TR (Turkey)

Dimensions

Length 30 mm

Wrench size, union nut 22 mm

Wrench size, support 22 mm

Hexagon angular dimension 24.5 mm

Length of the connecting thread 6.5 mm

Feed-through hole diameter 20.5 mm ... 20.7 mm

External cable diameter 6 mm ... 12 mm

10 mm ... 12 mm (for UL 514 B)

Ambient conditions

Degree of protection (IP) IP69 (DIN EN 60529 / IEC 60529)

IP68 (5 bar, 30 min.)

Degree of protection (NEMA) 4X

Ambient temperature (operation) -40 °C ... 100 °C (static)

General

No. of conductors 1

Cable gland material Nickel-plated brass

Material, insert Polyamide 6

Cable seal material Neoprene

Sealing material Perbunan (O-ring)

Shielded no

Thread type connection side Pg13.5

Thread type on connection side Pg13,5

Torque 5.5 Nm (Union nut: EN 62444)

5.5 Nm (Support: EN 62444)

8 Nm (for UL514 B: union nut)

Color silver

Assembly instructions 1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque

Manufacturer BIMED

Manufacturer Designation BSBC-04

Standards and Regulations

Halogen-free no

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127081000eCl@ss 6.0271...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INS-PG13,5-S68N-NNES-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.