

INDUSTRIAL COMPONENT DATA

G-INSEC-M25-S68N-NCRS-S 1411190 PHOENIX CONTACT

Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INSEC-M25-S68N-NCRS-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INSEC-M25-S68N-NCRS-S
Catalog number	1411190
Category	Cable gland
Minimum order	5 Pcs
Document ID	EO-3C41E92D76
Generated	2026-08-06

Product Overview

Cable gland

Cable gland, screwed connection material: Brass, nickel-plated, outer diameter of the cable 11 mm ... 16 mm, shielding: yes, connection thread: M25 x 1.5, color: silver, with O-ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Key Commercial Data

Orderkey 1411190

Packing unit 5 pc

Minimum order quantity 5 pc

Catalog page Page 698 (C-2-2017)

GTIN 4046356923217

Weight per Piece (excluding packing) 57.820 g

Custom tariff number 74199990

Country of origin DE (Germany)

Dimensions

Length 36 mm

Wrench size, union nut 27 mm

Wrench size, support 27 mm

Hexagon angular dimension 30 mm

Length of the connecting thread 7 mm

Feed-through hole diameter 25.1 mm ... 25.2 mm

External cable diameter 11 mm ... 16 mm

Ambient conditions

Degree of protection (IP) IP68 (5 bar, 30 minutes)

Ambient temperature (operation) -40 °C ... 100 °C (static)

General

No. of conductors 1

Cable gland material Nickel-plated brass

Material, insert Polyamide 6

Cable seal material CR / NBR

Sealing material Perbunan (O-ring)

Shielded yes

Thread type connection side M25 x 1.5

Thread type on connection side M25

Torque 6.7 Nm (Union nut: EN 62444)

6.7 Nm (Support: EN 62444)

Color silver

Impact category 6

Execution of the strain relief A

Connection Method 1

Cut the outer sheath, but do not remove it. Feed the cable through the screw connection and then remove the outer sheath. Now pull the cable back until the connection is established between the cable shield and the contact spring.

Method 2

Push the braided shield back around 15 ... 20 mm over the outer sheath. Insert the cables into the screw connection until the connection is established between the cable shield and the contact spring.

Standards and Regulations

Halogen-free no

Connection in....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INSEC-M25-S68N-NCRS-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.