

INDUSTRIAL COMPONENT DATA

G-INSEC-M50-L68N-NCRS-S 1411193 PHOENIX CONTACT

Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INSEC-M50-L68N-NCRS-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INSEC-M50-L68N-NCRS-S
Catalog number	1411193
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-D068D20D74
Generated	2026-08-05

Product Overview

Cable gland

Cable gland, screwed connection material: Brass, nickel-plated, outer diameter of the cable 24 mm ... 35 mm, shielding: yes, connection thread: M50 x 1.5, color: silver, with O-ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Key Commercial Data

Orderkey 1411193

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 698 (C-2-2017)

GTIN 4046356923248

Weight per Piece (excluding packing) 334.500 g

Custom tariff number 74199990

Country of origin DE (Germany)

Dimensions

Length 49 mm

Wrench size, union nut 55 mm

Wrench size, support 55 mm

Hexagon angular dimension 60 mm

Length of the connecting thread 9 mm

Feed-through hole diameter 50.1 mm ... 50.3 mm

External cable diameter 24 mm ... 35 mm

Ambient conditions

Degree of protection (IP) IP68 (5 bar, 30 minutes)

Ambient temperature (operation) -40 °C ... 100 °C (static)

General

No. of conductors 1

Cable gland material Nickel-plated brass

Material, insert Polyamide 6

Cable seal material CR / NBR

Sealing material Perbunan (O-ring)

Shielded yes

Thread type connection side M50 x 1.5

Thread type on connection side M50

Torque 13.5 Nm (Union nut: EN 62444)

13.5 Nm (Support: EN 62444)

Color silver

Impact category 7

Execution of the strain relief A

Connection Method 1

Cut the outer sheath, but do not remove it. Feed the cable through the screw connection and then remove the outer sheath. Now pull the cable back until the connection is established between the cable shield and the contact spring.

Method 2

Push the braided shield back around 15 ... 20 mm over the outer sheath. Insert the cables into the screw connection until the connection is established between the cable shield and the contact spring.

Standards and Regulations

Halogen-free no

Con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INSEC-M50-L68N-NCRS-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.