

INDUSTRIAL COMPONENT DATA

G-INS-M16-S68N-NNES-S 1411162 PHOENIX CONTACT Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INS-M16-S68N-NNES-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INS-M16-S68N-NNES-S
Catalog number	1411162
Category	Cable gland
Minimum order	10 Pcs
Document ID	EO-13A8B47D60
Generated	2026-08-06

Product Overview

Cable gland

Cable gland, screwed connection material: Brass, nickel-plated, outer diameter of the cable 5 mm ... 10 mm, shielding: no, connection thread: M16 x 1.5, color: silver, with O-ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Key Commercial Data

Orderkey 1411162

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 696 (C-2-2017)

GTIN 4046356922975

Weight per Piece (excluding packing) 27.140 g

Custom tariff number 74199990

Country of origin TR (Turkey)

Dimensions

Length 34 mm

Wrench size, union nut 20 mm

Wrench size, support 20 mm

Hexagon angular dimension 22 mm

Length of the connecting thread 7 mm

Feed-through hole diameter 16.1 mm ... 16.3 mm

External cable diameter 5 mm ... 10 mm

6 mm ... 10 mm (for UL 514 B)

Ambient conditions

Degree of protection (IP) IP69 (DIN EN 60529 / IEC 60529)

IP68 (5 bar, 30 min.)

IP66

Degree of protection (NEMA) 4X

Ambient temperature (operation) -40 °C ... 100 °C (static)

General

No. of conductors 1

Cable gland material Nickel-plated brass

Material, insert Polyamide 6

Cable seal material Neoprene

Sealing material Perbunan (O-ring)

Shielded no

Thread type connection side M16 x 1.5

Thread type on connection side M16

Torque 7 Nm (Union nut: EN 62444)

7 Nm (Support: EN 62444)

8 Nm (for UL514 B: union nut)

Color silver

Impact category 6

Execution of the strain relief A

Assembly instructions 1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque

Manufacturer BIMED

Manufacturer Designation BMBC-E1

Standards and Regulations

Halogen-free no

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold value...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INS-M16-S68N-NNES-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.