

INDUSTRIAL COMPONENT DATA

G-ESISEC-M20-S68N-NEPDS-S 1415163 PHOENIX CONTACT

Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-ESISEC-M20-S68N-NEPDS-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-ESISEC-M20-S68N-NEPDS-S
Catalog number	1415163
Category	Cable gland
Minimum order	10 Pcs
Document ID	EO-26E58EA585
Generated	2026-08-06

Product Overview

Cable gland

Cable gland, screwed connection material: Brass, nickel-plated, application: Ex, outer diameter of the cable 6 mm ... 13 mm, shielding: yes, connection thread: M20 x 1.5, color: silver, with O-ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial plug-in connectors/interfaces**

Additional Product Information

Key Commercial Data

Orderkey 1415163

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 555 (C-3-2017)

GTIN 4055626037943

Weight per Piece (excluding packing) 59.240 g

Custom tariff number 74199990

Country of origin DE (Germany)

Dimensions

Length 43 mm

Thread pitch 1.5 mm

Wrench size, union nut 24 mm

Wrench size, support 24 mm
Hexagon angular dimension 27 mm
Length of the connecting thread 12 mm
External cable diameter 6 mm ... 13 mm
Cable types that can be used for unarmored cables
Hole diameter 20.1 mm ... 20.3 mm
Ambient conditions
Degree of protection (IP) IP66
IP68 (5 bar / 0.5 h)
Ambient temperature (operation) -40 °C ... 75 °C (static)
General
Cable gland material Nickel-plated brass
Material grommet GRP EPDM (O-ring)
Cable seal material EPDM
Material, insert PA
Thread type connection side M20 x 1.5
Torque 8 Nm (Support sleeve)
Tightening torque, union nut 8.00 Nm
Color silver
Connection Mounting the screw connection:
- Mount cable gland support
- Strip outer cable sheath. Expose around 7 mm of the cable shield.
- Push the outer cone over the braided shield
- Push the inner cone under the shield
- Insert both, together with the cable, in the mounted screw connection support
- Tighten union nut with the required torque
Manufacturer WSKA
Manufacturer Designation EMSKE-L 20 EMV-Z
Suited for EX-applications yes
Standards and Regulations
ATEX II 2 G/D EEx e II IP68
IECEX Ex e IIC Gb, Ex tb IIIC Db
Environmental Product Compliance
REACH SVHC Lead 7439-92-1
C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-ESISEC-M20-S68N-NEPDS-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.