

INDUSTRIAL COMPONENT DATA

G-ESIS-M25-M68N-NEPDS-S 1415126 PHOENIX CONTACT

Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-ESIS-M25-M68N-NEPDS-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-ESIS-M25-M68N-NEPDS-S
Catalog number	1415126
Category	Cable gland
Minimum order	10 Pcs
Document ID	EO-53EDB280ED
Generated	2026-08-05

Product Overview

Cable gland

Cable gland, screwed connection material: Brass, nickel-plated, application: Ex, outer diameter of the cable 10 mm ... 17 mm, shielding: no, connection thread: M25 x 1.5, color: silver, with O-ring

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1415126

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 555 (C-3-2017)

GTIN 4055626037875

Weight per Piece (excluding packing) 68.910 g

Custom tariff number 74199990

Country of origin DE (Germany)

Dimensions

Length 38 mm

Thread pitch 1.5 mm

Wrench size, union nut 29 mm

Wrench size, support 29 mm

Hexagon angular dimension 32 mm

Length of the connecting thread 12 mm

External cable diameter 10 mm ... 17 mm

Cable types that can be used for unarmored cables

Hole diameter 25.1 mm ... 25.3 mm

Ambient conditions

Degree of protection (IP) IP66

IP68 (5 bar / 0.5 h)

Ambient temperature (operation) -40 °C ... 75 °C (static)

General

Cable gland material Nickel-plated brass

Material grommet GRP EPDM (O-ring)

Cable seal material EPDM

Material, insert PA

Thread type connection side M25 x 1.5

Torque 10 Nm (Support sleeve)

Tightening torque, union nut 10.00 Nm

Color silver

Manufacturer WSKA

Manufacturer Designation EMSKE-L 25

Suited for EX-applications yes

Standards and Regulations

ATEX II 2 G/D EEx e II IP68

IECEX Ex e IIC Gb, Ex tb IIIC Db

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127149100eCl@ss 6.027149100eCl@ss 7.027149109eCl@ss 8.027149109eCl@ss 9.027144432

ETIM 5.0EC000441ETIM 6.0EC000441

UNSPSC 13.239121311

ETIM for 1415126 Cable glands and cable....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-ESIS-M25-M68N-NEPDS-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.