

INDUSTRIAL COMPONENT DATA

G-ESS-M40-L66L-NTES-S 1411081 PHOENIX CONTACT Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-ESS-M40-L66L-NTES-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-ESS-M40-L66L-NTES-S
Catalog number	1411081
Category	Cable gland
Minimum order	2 Pcs
Document ID	EO-049CEF0E6A
Generated	2026-08-06

Product Overview

Cable gland

Cable gland, screwed connection material: Brass, nickel-plated, application: Ex, outer diameter of the cable 23.5 mm ... 32.2 mm, shielding: no, connection thread: M40 x 1.5, color: silver

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1411081

Packing unit 2 pc

Minimum order quantity 2 pc

Catalog page Page 556 (C-3-2017)

GTIN 4046356921954

Weight per Piece (excluding packing) 208.350 g

Custom tariff number 74152900

Country of origin GB (United Kingdom)

Dimensions

Length 43 mm

Thread pitch 1.5 mm

Wrench size, union nut 50 mm

Wrench size, support 50 mm
Hexagon angular dimension 55 mm
Length of the connecting thread 15 mm
External cable diameter 23.5 mm ... 32.2 mm
Cable types that can be used for unarmored cables
Ambient conditions
Degree of protection (IP) IP66 (using the corresponding A-SEW-...P-W flat gasket)
IP67 (using the corresponding A-SEW-...P-W flat gasket)
IP68 (using the corresponding A-SEW-...P-W flat gasket)
Ambient temperature (operation) -60 °C ... 130 °C (static)
General
Cable gland material Nickel-plated brass
Cable seal material EPDM
Thread type connection side M40 x 1.5
Color silver
Impact energy 20.00 J
Assembly instructions Sealed to IP66/IP67/IP68 thanks to the use of the A-SEW-40-P-W flat gasket (item 1411286)
Standards/specifications EN 60079-0, -1, -7, -15, -31
IEC 60079-0, -1, -7, -15, -31
EN 50262
BS 6121: Part 1:1989
IEC 62444
Manufacturer CMP
Manufacturer product number 40A2F1RA5
Manufacturer Designation 40 A2F N. PLTD GLAND
Suited for EX-applications yes
Standards and Regulations
Standards/regulations EN 60079-0, -1, -7, -15, -31
IEC 60079-0, -1, -7, -15, -31
EN 50262
BS 6121: Part 1:1989
ATEX Sira 13ATEX1068X
Sira 13ATEX4074X
Ex II 2/3G, II 1D, Ex....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-ESS-M40-L66L-NTES-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.