


INDUSTRIAL COMPONENT DATA

G-INS-N1/2-S68L-PNES-GY 1411153 PHOENIX CONTACT

Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INS-N1/2-S68L-PNES-GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INS-N1/2-S68L-PNES-GY
Catalog number	1411153
Category	Cable gland
Minimum order	10 Pcs
Document ID	EO-E79A0DCC2A
Generated	2026-08-05

Product Overview

Cable gland

Cable gland, screw connection material: PA, outer diameter of the cable 10 mm ... 14 mm, shielding: no, connection thread: 1/2 in. NPT, color: silver gray RAL 7001

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1411153

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 683 (C-4-2015)

GTIN 4046356922883

Weight per Piece (excluding packing) 14.980 g

Custom tariff number 39269097

Country of origin TR (Turkey)

Dimensions

Length 47 mm

Wrench size, union nut 27 mm

Wrench size, support 27 mm

Hexagon angular dimension 30.8 mm

Length of the connecting thread 15 mm

External cable diameter 10 mm ... 14 mm

10 mm ... 14 mm (for UL 514 B)

Ambient conditions

Degree of protection (IP) IP68 (5 bar / 0.5 h)

IP66

Ambient temperature (operation) -20 °C ... 100 °C (static)

General

No. of conductors 1

Cable gland material PA

Cable seal material Neoprene

Flammability rating according to UL 94 V2

V2 (Housing)

Shielded no

Thread type connection side 1/2 inch NPT

Thread type on connection side 1/2 inch NPT

Torque 2 Nm (Union nut: EN 62444)

2 Nm (Support: EN 62444)

9 Nm (for UL514 B: union nut)

Color silver-gray RAL 7001

Assembly instructions 1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque

Manufacturer BIMED

Manufacturer Designation BSPC-02

Standards and Regulations

Halogen-free no

Connection in acc. with standard CSA

Flammability rating according to UL 94 V2

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127149100eCl@ss 6.027149100eCl@ss 7.027149109eCl@ss...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INS-N1/2-S68L-PNES-GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.