

INDUSTRIAL COMPONENT DATA

G-ESIS-M63-L68L-PEPDS-BK 1415113 PHOENIX CONTACT

Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-ESIS-M63-L68L-PEPDS-BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-ESIS-M63-L68L-PEPDS-BK
Catalog number	1415113
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-0DD4A08797
Generated	2026-08-02

Product Overview

Cable gland

Cable gland, screwed connection material: PA, application: Ex, outer diameter of the cable 34 mm ... 48 mm, shielding: no, connection thread: M63 x 1.5, color: black, with flat gasket

Cable gland, Material gland: PA, Application: Ex, Cable outer diameter 34 mm ... 48 mm, shielding: no, connection thread: M63 x 1.5, colour: deep black, with flat gasket

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1415113

Packing unit 1 pc

Catalog page Page 554 (C-3-2017)

GTIN 4055626037752

Weight per Piece (excluding packing) 178.800 g

Custom tariff number 39269097

Country of origin DE (Germany)

Dimensions

Length 67 mm

Thread pitch 1.5 mm

Wrench size, union nut 68 mm
Wrench size, support 68 mm
Hexagon angular dimension 75 mm
Length of the connecting thread 18 mm
External cable diameter 34 mm ... 48 mm
Cable types that can be used for unarmored cables
Hole diameter 63.1 mm ... 63.3 mm
Ambient conditions
Degree of protection (IP) IP66
IP68 (5 bar / 0.5 h)
Ambient temperature (operation) -40 °C ... 75 °C (static)
General
Material PA (Screw connection, halogen-free)
Cable gland material PA
Material grommet GRP EPDM (Cable seal, halogen-free)
Glow wire ignition temperature GWIT according to EN 60695-2-13 750.00
Thread type connection side M63 x 1.5
Torque 17 Nm (Support sleeve)
Tightening torque, union nut 16.00 Nm
Color black
Impact energy 7.00 J (at -40 °C ... +75 °C)
Manufacturer WISKA
Manufacturer Designation ESKE/1-L-e 63
Suited for EX-applications yes
Standards and Regulations
ATEX II 2 G Ex e IIC Gb, II 2 D Ex tb IIIC Db
IECEx Ex e IIC Gb, Ex tb IIIC Db
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127149100eCl@ss 6.027149100eCl@ss 7.027149109eCl@ss 8.027149109eCl@ss 9.027144432
ETIM 5.0EC000441ETIM 6.0EC000441
UNSPSC 13.23912131...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-ESIS-M63-L68L-PEPDS-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.