

INDUSTRIAL COMPONENT DATA

G-INTRO-M20-S68N-PEPDS-BK 1415189 PHOENIX CONTACT

Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INTRO-M20-S68N-PEPDS-BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INTRO-M20-S68N-PEPDS-BK
Catalog number	1415189
Category	Cable gland
Minimum order	10 Pcs
Document ID	EO-22C834FDEE
Generated	2026-08-05

Product Overview

Cable gland

Cable gland, screwed connection material: PA, clamping screw material: PA, cable outer diameter 6 mm ... 13 mm, shielding: no, connection thread: M20 x 1.5, colour: deep black, with external traction compensation

Cable gland, screw connection material: PA, application: Standard, outer diameter of cable 6 mm ... 13 mm, shielding: no, connection thread: M20 x 1.5, colour: deep black, with external traction compensation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1415189

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 706 (C-2-2017)

GTIN 4055626038179

Weight per Piece (excluding packing) 17.870 g

Custom tariff number 39269097

Country of origin DE (Germany)

Dimensions

Length 49 mm

Length without connecting thread 39 mm
Wrench size, union nut 24 mm
Wrench size, support 24 mm
Hexagon angular dimension 27 mm
Length of the connecting thread 10 mm
Feed-through hole diameter 20.1 mm ... 20.2 mm
External cable diameter 6 mm ... 13 mm
7.5 mm ... 11.3 mm (for UL 514 B)
Clamping range of the strain relief clip 6.00 mm ... 13.00 mm
Ambient conditions
Degree of protection (IP) IP68 (5 bar / 0.5 h)
IP69 (DIN EN 60529 / IEC 60529)
Ambient temperature (operation) -40 °C ... 100 °C (static)
General
Type with external strain relief
No. of conductors 1
Material PA
Cable gland material PA
Material, pressure screw PA
Sealing material EPDM (Cable seal, halogen-free)
Glow wire ignition temperature GWIT according to EN 60695-2-13 750.00
Shielded no
Thread type connection side M20 x 1.5
Thread type on connection side M20
Torque 4 Nm (Union nut: EN 62444)
4 Nm (Support: EN 62444)
0.5 Nm (Screw for clip)
Color jet black
Impact category 2
Execution of the strain relief B
Manufacturer WSKA
Manufacturer Designation ESKVZ 20
Standards and Regulations
Halogen-free yes
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Class...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INTRO-M20-S68N-PEPDS-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.